Pneumatic Wrench

- Non Impacting Tool
- Zero Hammering or Vibration.
- Smooth Continuous Flow of Controlled Torque from 200 ft lbs to 1000 ft lbs.
- Accuracy of +/- 5%.
- Reduced Noise Levels—80 db.
- High RPM—Reduce Bolting Time.
- Diverse Tool for Multiple Applications.

PN - 13691	10GX-NX TOOL KIT 200-1000 ft lbs (includes cage, hose, filter assembly).	
PN - 13366	Standard Reaction Arm.	•
PN - 13512	Standard Nose Extension Reaction Arm.	•
PN - 11842	Nose Extension Wheel Nut Reaction Arm.	1
PN - 12818	10GX (Tool Only) 200-1000 ft lbs (includes cage, hose, filter assembly).	•
PN - 14195	Nose Extension.	•













Articulated Trucks

- Wheel Nuts
- Maintenance
- Repairs
- Safety
- Ergonomics
- Reliability

Dozers

- Track Pad Bolts
- Cutter Edge Bolts
- Final Drives
- Strut Tensioning
- Maintenance
- Repairs

Excavators

- Track Pad Bolts
- Cutter Edge Bolts
- Maintenance
- Repair
- Safety
- Reliability

Loaders

- Wheel Nuts
- Swing Arm Bolts
- Repair
- Maintenance
- Safety
- Accuracy









Powerful

Ergonomic

Reliable

Safe