



# RAPID-TORC<sup>®</sup>

## BIG NUTS - BIG TOOLS<sup>™</sup>

### RAPID-TORC<sup>®</sup> RTX Series

If you can fit just with a slugging wrench.....  
..... you will fit with our Low Profile RTX !

**THE RIGHT TOOL FOR ALL YOUR CONFINED AREAS**



**Rapid-Torc Low Clearance RTX Series...wherever you cannot fit!**

### **Key Benefits**

- 6 Models from 167 ft-lbs up to 31,000 ft-lbs
- Unlimited Choice of Ratchet Links in 1/16" increments or Metric size.
- Four Mechanical moving parts (Hand-Free operations)
- One Way Ratchet System for a Single Operator "Hands Free Operation"
- Double Acting Operation
- Automatic "Ratchet Link-Piston Rod End" Attachment and Disengagement
- Slim profile for Ratchet link and Power-Head
- Snap-in, Interchangeable Ratchet Link. No tools required.
- Very high ratio Torque to weight
- Constant maximum torque value for each model no matter the hex size
- Tight Radius Ratchet Link
- Strong Unibody Design
- Anti Side Load Resistant Link Design
- In Line Reaction Pad for maximum strength
- Robust Double Tooth Ratchet Mechanism
- Never-Lock Torque Mechanism
- Rapid-Swivels Multi Axis 360°x180°
- Housing made of Aircraft Quality Aluminum
- Output Accuracy certified at +/- 3%
- Repeatability certified at +/- 1%
- Plated finish for a Fully Corrosion resistance
- CE approved





# RAPID-TORC®

## BIG NUTS - BIG TOOLS™

### RAPID-TORC® RTX Series

Models		RTX-2	RTX-4	RTX-8	RTX-14	RTX-30
Ratchet Link Hex Size	Inch	3/4"-2 3/4"	1"-3 1/8"	1 5/8"-4 1/8"	2 1/2"-4 3/4"	3 1/2"-6 1/2"
	mm	19-60	25-80	46-110	60-120	90-165
Min Torque	Ft-lbs	255	580	1143	2010	4770
	Nm	346	786	1549	2725	6466
Max Torque	Ft-lbs	1710	3855	8151	13400	31800
	Nm	2318	5226	11049	18165	43108
L	inch	7,20	9,76	12,12	14,64	NC
	mm	183	248	308	372	NC
R	inch	0,35	0,47	0,59	0,72	nc
	mm	9	12	15	18,5	NC
W1	inch	1,26	1,65	2,08	2,48	3,26
	mm	32	42	53	63	83
W2	inch	1,92	2,56	3,22	3,89	5,28
	mm	49	65	82	99	132
Weight with Ratchet Link	Lbs	4,5	9,7	19,5	33	78
	Kg	2,2	4,9	10	17,5	39

